

Specifications

| Model | ERT-100 PLUS Robotic Tracking System |
|---------------------------|--|
| Pan-Tilt Head | U-shaped 2-axis with built-in sensor, brushless motor, precision reducer |
| Pan / Tilt Speed | 0.01°/s~60°/s |
| Load Capacity | 60kg/132lbs |
| Lifting Column Range | Electric 3-section |
| Lift Speed | 0.02mm/s-150mm/s |
| Track Speed | 0.02mm/s-2000mm/s |
| Stroke | 450mm |
| Min. Lens Mounting Height | 720mm |
| Max. Lens Mounting Height | 1600mm |
| Tilt Range | +45° ~ -45° |
| Tracking Dolly | Aluminum base, 8 load-bearing wheels, steerable |
| Tracking Dolly Dimensions | 790mmx453mm (LxW) |
| Track | CNC, 360mm spacing, 2m/section(Standard:10m) |
| Remote Control Panel | 11-inch LCD touchscreen |
| Power Supply | AC 110V-220V |
| Operating Power | 1.0kw |
| Camera Compatibility | Studio cameras (Canon, Fujinon Full-Servo Lenses); ENG, EFP cameras |
| Packaging | Aluminum case |

NINGBO EIMAGE STUDIO EQUIPMENT CO., LTD.

Address: No.1230 South Cihai Rd,Luotuo Industry zone, Zhenhai,
Ningbo, China. 315202
Tel:86-574-86590061,86-574-86590031
E-mail: sales@eimagevideo.com

Visit www.eimagevideo.com for more information



E-IMAGE Official QR Code



The magic life in the image world

E-IMAGE

ERT-100 PLUS

Robotic Tracking System

www.eimagevideo.com



ERT-100 PLUS Robotic Tracking System

The modular robotic tracking system, consisting of a Pan-Tilt head, lifting column, tracking dolly, and multi-function controller, offers ultimate control with 7-axis precision. It enables seamless manipulation of horizontal movement, lifting, pan, tilt, zoom, focus, and iris. It aims to achieve unmanned and automated program recording,making it highly versatile across various program genres like news, interviews, sports, conferences, variety shows, and current affairs.

Pan-Tilt Head

- 60kg/132lbs load capacity, 0.01°/s~60°/s.
- U-shaped 2-axis with built-in sensor, brushless motor, precision reducer.
- Supports broadcast-level lens control of pan, tilt, zoom, focus, and iris.
- Compatible with Canon and Fujinon full-servo lenses, ENG, EFP cameras.

Lifting Column

- Electric 3-section design, high-hardness aluminum alloy material.
- Lift speed: 0.02mm/s-150mm/s.
- Working height: 720mm-1600mm, stroke: 450mm.
- Built-in integrated circuit and sensor, ultra-quiet motor.
- Simple and stable modular installation.

Tracking Dolly

- Track speed: 0.02mm/s-2000mm/s
- Built-in brake and deceleration system.
- Soft start and stop for smooth and stable movement.
- 4 sets of integrated silent, steerable, and height-adjustable wheels.
- Neat cable management with drag poles design.

Remote Control Panel



- 11" LCD touchscreen for visual parameter settings.
- Dual joysticks operation, variable speed control.
- Remote 7-axis precision control of lifting column, tracking dolly, pan-tilt head, and lens.
- Supports 300 presets and 150 track settings, allowing for single-point, single-pass continuous, or multi-loop movements.



Ground Tracks

- High-hardness aluminum alloy track with a one-piece forged structure and CNC machining.
- Integrated intelligent deceleration module and brake system.
- Standard single section track length: 2m (10 meters in total,straight).
- Extendable with optional 1-meter or 2-meter sections.
- Optional curved track available.

Curved and Straight Tracks Diagrams



What's Included

| | | |
|---|---|---------|
| ① | Pan-Tilt Head | x1 set |
| ② | Lifting Column | x1 set |
| ③ | Tracking Dolly | x1 set |
| ④ | Control Panel | x1 set |
| ⑤ | Track Damper | x2 sets |
| ⑥ | Regular Track | x5 sets |
| ⑦ | Controller Power Cable | x1 set |
| ⑧ | Track Turnbuckle | x12 pcs |
| ⑨ | Track Stopper Blocks | x12 pcs |
| ⑩ | 5mm Allen Wrench | x1 pc |
| ⑪ | Network Cable | x1 roll |
| ⑫ | Tracking Dolly Power Cable | x1 roll |
| ⑬ | Track Synchronous Belt | x1 set |
| ⑭ | Nylon Cable Ties | x10 pcs |
| ⑮ | Velcro Cable Sleeve | x1 set |
| ⑯ | Lense Cable | x5 pcs |
| ⑰ | Power Cable Cor Camera | x1 set |
| ⑱ | Cable For Connecting Pan&Tilt Head and Tracking Dolly | x5 pcs |
| ⑲ | PS-C | x1 set |
| ⑳ | Aluminum Case | x5 pcs |

Controller Power Cable(1.5M) x1 set
⑦

Track Turnbuckle x12 pcs
⑧

Track Stopper Blocks x12 pcs
⑨

5mm Allen Wrench x1 pc
⑩

Network Cable x1 roll
⑪

Tracking Dolly Power Cable(15M) x1 roll
⑫

Track Synchronous Belt(12M) x1 set
⑬

Nylon Cable Ties x10 pcs
⑭

Velcro Cable Sleeve(12M) x1 set
⑮

Details

Pan-Tilt Head x1 set
①

Lifting Column x1 set
②

Tracking Dolly x1 set
③

Control Panel x1 set
④

Track Damper x2 sets
⑤

Regular Track (2M) x5 sets
⑥

Lense Cable x1 set
⑯

Power Cable For Camera x1 set
⑰

Cable For Connecting Pan&Tilt Head and Tracking Dolly x1 set
⑱

PS-C x1 set
⑲

Aluminum Case (Pan-Tilt Head+Control Panel)
②

Aluminum Case (Tracking Dolly+Track Damper)

Aluminum Case (Lifting Column+Accessories)

Aluminum Case (Regular Track)

Aluminum Case (Regular Track)

Aluminum Case x5 pcs
②