



MTR-20 Dual-Channel Wireless Kit

Component : DR200 + ST100 + MT900



Features

- 100 channels.
- Mute switch.
- 10 hours of continuous use.
- Built-in 1800mAh lithium battery.
- Low-cut filter reduces noise caused by wind or machinery-off/ Low (75Hz)/ High (150 Hz).



DR200

This wireless system offers AB 100 frequencies to choose from and avoid RF interference, for several devices to work together.



ST100

Low-cut filter reduces noise caused by wind or machinery-Off / Low (75Hz) / High (150 Hz).



Low-cut filter reduces noise caused by wind or machinery-Off / Low (75Hz) / High (150 Hz).



The use distance in open and unobstructed spaces is 120m;
The use distance in obstructed places is 60m.



Power a condenser microphone with full 48V phantom power supplied from the plug-on transmitter.



UHF frequencies (UHF500~900MHz), depending on the country / region.

Specifications

Model	DR200	ST100
Channel	A/ B 100CHs	100CHs
Wireless Frequency Range	UHF500~900MHz	UHF500~900MHz
Frequency Response	60Hz~15KHz	60Hz~15KHz
Signal/Noise	/	/
Transmitting Power	10mW(Low) / 30mW(High)	10mW(Low) / 30mW(High)
Stray Radiation	< -60dB	< -60dB
Audio T.H.D	< 0.5%@1KHz	< 0.5%@1KHz
High Pass Filter	-75Hz(Low) / -150Hz(High)	-75Hz(Low) / -150Hz(High)
Audio Output	Mono	Mono
Display Screen	LCD	LCD
Working Distance	In line-of-sight area(120m) / In barrier area(60m)	In line-of-sight area(120m) / In barrier area(60m)
Power	Type-C 3.5 hours full, DC 5V@1000mA	Type-C 3.5 hours full, DC 5V@1000mA
Battery	Built-in li-ion battery, 3.7V, 1800mA/Hour	Built-in li-ion battery, 3.7V, 1800mA/Hour
Working Time	10Hours	10Hours
Size	96x60x19mm	96x60x19mm
Operating Temperature	0-50℃	0-50℃
Material	Aluminum	Aluminum

Model	MT900
Wireless Frequency Range	UHF500-900MHz
Reciver	SR100, DR200
Input Socket	XLR
Transmitter Power	10mW~30mW
Harmonic Radiation	<-55dBc
Input Mode	Mic / Line
Max Input	MIC=130mV@1KHz / LINE=1500mV@1KHz
Maximum Offset	± 45KHz@1KHz
Phantom Power Voltage	+48V
Display Screen	LCD
Battery	AA1.5V/1.2V Ni-MH battery
Working Time	10Hours
Size	44x44x110mm
Operating Temperature	0-50℃
Material	Aluminum

What's included



DR200 x1 ST100 x1 MT900 x1



XLR to 3.5mm Cable x1



USB to Type-C Cable x2



TRRS Cable(For Phone) x1
TRS Cable(For Camera) x1



Clip-on Microphone Cable x1



Cold Shoe Adapter x1



Belt Clip x1